

5" HEXACONE-Tief-/Mitteltöner für kleine Monitor-Boxen sowie als Mitteltöner in Mehrweganwendungen.

5" HEXACONE-bass /midrange unit for small monitor speakers as well as for application as a midrange driver in multiple way constructions.

Nennbelastbarkeit / Nominal rated power	50 W
Nennimpedanz / Nominal impedance	8 Ω
Frequenzbereich / Frequency range	50-4000 Hz
Empfindlichkeit 1W/1m / Sensivity 1W/1m	87 dB
Resonanzfreq. TSP / Resonance freq. TSP	52 Hz
Qms	2,29
Qes	0,46
Qts	0,38
Vas	8,7 l
Gleichstromwiderstand / DC resistance	6,6 Ω
Lineare Auslenkung / Linear excursion	3 mm
BL Produkt / BL product	4,5 Tm
Bewegte Masse / Moving mass incl. air	9,6 g
Effektive Abstrahlfläche / Effective piston area	82 cm ²
Membranmaterial / Dome material	HEXACONE
Schwingspuleninduktivität / Voice coil inductivity	0,48 mH
Schwingspulen- \emptyset / voice coil \emptyset	25 mm
Trägermaterial / Former material	Aluminium
Polplattendicke / Air gap height	6 mm
Magnet- \emptyset / Magnet \emptyset	90 mm
Korbmaterial / Chassis material	Aluminium diecast

5-880/25 Hex

